

E2 MediFlo® Valve

Description:

Capable of dispensing liquids, gases or powders at controlled dosages, the MediFlo® elastomeric valve is ideally suited for medical applications that require effective drip-proof, bi-directional or one-way flow control with few components or moving parts. This valve replaces multi-component ball and spring or other complex check valves & flow control valves.

Valve Characteristics:

- **Outside Diameter:** .634" (16.1 mm)
- **Material:** Silicone
- **Valve type:** E style, rolling sleeve
- **Opening pressure:** Medium
(low = 1"-16" (0-.58 PSI), medium = 17"-26" (.6 - .94 PSI) and high = 27" + (1 + PSI)
- **Unique Properties:** Compatible with a variety of viscosities and available in many durometers
- **Applications:** Antibacterial cleansing solutions, fluid filtration, purification systems filtration devices, wound drainage, renal & pulmonary devices, enteral feeding devices and many new applications under confidential development with customers

Related Documents:

- **Engineering drawing:** RCA-1708 (+REV)
- **Customer drawing:** CS-2331-1708.drw (+REV)
- **LMS project number:** 99-038

Valve Performance by Slit Size

SLIT SIZE inches / mm	OPEN (H ₂ O Column Height) inches / mm / PSI	CLOSE (H ₂ O Column Height) Inches / mm / PSI	Constant Flow (@ 30" of H ₂ O) ml / sec
.070 / 1.778	20 / 508 / .72	16 / 406 / .56	1
.130 / 3.302	20 / 508 / .72	16 / 406 / .56	5
.160 / 4.064	19 / 483 / .54	15 / 381 / .54	7
.187 / 4.750	19 / 483 / .54	15 / 381 / .54	9
.220 / 5.588	19 / 483 / .54	15 / 381 / .54	10
.250 / 6.350	19 / 483 / .54	15 / 381 / .54	11
.280 / 7.112	19 / 483 / .54	15 / 381 / .54	13
.300 / 7.620	19 / 483 / .54	14 / 356 / .50	14

UNCONTROLLED, SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

