

# V23 *MediFlo*® Valve

## Description:

Capable of dispensing liquids, gases or powders at controlled dosages, the MediFlo® elastomeric valve is ideally suited for medical applications that require effective drip-proof, bi-directional or one-way flow control with few components or moving parts. This valve replaces multi-component ball and spring or other complex check valves & flow control valves.

## Valve Characteristics:

- **Outside Diameter:** .634" (16.1 mm)
- **Material:** Silicone
- **Valve type:** C style, rolling sleeve
- **Opening pressure:** Low  
(low = 1"-16" (0-.58 PSI), medium = 17"-26" (.6 - .94 PSI) and high = 27" + (1 + PSI)
- **Unique Properties:** Compatible with a variety of viscosities and available in many durometers. Ideal for low opening pressure applications
- **Applications:** Antibacterial cleansing solutions, fluid filtration, purification systems filtration devices, wound drainage, renal & pulmonary devices, enteral feeding devices and many new applications under confidential development with customers

## Related Documents:

- **Engineering drawing:** ECA-4199 (+REV)
- **Customer drawing:** CBA-4199 (+REV)
- **LMS project number:** 00-006

## Valve Performance by Slit Size

SLIT SIZE inches / mm	OPEN (H <sub>2</sub> O Column Height) inches / mm / PSI	CLOSE (H <sub>2</sub> O Column Height) Inches / mm / PSI	Constant Flow (@ 30" of H <sub>2</sub> O) ml / sec
.160 / 4.064	12 / 305 / .43	9 / 229 / .32	6.3
.220 / 5.588	12 / 305 / .43	9 / 229 / .32	11.1

UNCONTROLLED, SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

