

V23 SimpliSqueeze® Valve

Description:

Capable of dispensing liquids, gases or powders at controlled dosages, the SimpliSqueeze® elastomeric valve is ideally suited for packaging applications that require effective drip-proof, bi-directional or one-way flow control with few components or moving parts. This valve replaces multi-component ball and spring or other complex check valves & flow control valves.

Valve Characteristics:

- **Outside Diameter:** .634" (16.1 mm)
- **Material:** Silicone
- **Valve type:** C style, rolling sleeve
- **Opening pressure:** Low
(low = 1"-16" (0-.58 PSI), medium = 17"-26" (.6 - .94 PSI) and high = 27" + (1 + PSI))
- **Unique Properties:** The C style sleeve allows for low opening pressure and controlled dispensing.
- **Applications:** Powder, Body wash, thin lotions where more control is desired.
-

Related Documents:

- **Engineering drawing:** ECA-4199 (+REV)
- **Customer drawing:** CBA-4199 (+REV)
- **Project number:** 00-006

Valve Performance by Slit Size

SLIT SIZE inches / mm	OPEN (H ₂ O Column Height) inches / mm / PSI	CLOSE (H ₂ O Column Height) Inches / mm / PSI	Constant Flow (@ 30" of H ₂ O) ml / sec
.160 / 4.064	12 / 305 / .43	9 / 229 / .32	6.3
.220 / 5.588	12 / 305 / .43	9 / 229 / .32	11.1

UNCONTROLLED, SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

