

E6 *SureFlo*® Valve

Description:

Capable of dispensing liquids, gases or powders at controlled dosages, the SureFlo® elastomeric valve is ideally suited for applications that require effective drip-proof, bi-directional or one-way flow control with few components or moving parts. This valve replaces multi-component ball and spring or other complex check valves & flow control valves.

Valve Characteristics:

- **Outside Diameter:** .375" (9.53 mm)
- **Material:** Silicone
- **Valve type:** E style, rolling sleeve
- **Opening pressure:** Medium
(low = 1"-16" (0-.58 PSI), medium = 17"-26" (.6 - .94 PSI) and high = 27" + (1 + PSI)
- **Unique Properties:** This design allows the valve head to be closer to the closure deck and be more visible.
- **Applications:** This valve is best suited for thin to medium products like shampoo, body wash, lotions, sauces, toothpaste and condiments.

Related Documents:

- **Engineering drawing:** ECA-3969
- **Customer drawing:** CBA-3969
- **LMS project number:** 00-090

Valve Performance by Slit Size

| SLIT SIZE inches / mm | OPEN (H ₂ O Column Height) inches / mm / PSI | CLOSE (H ₂ O Column Height) Inches / mm / PSI | Constant Flow (@ 30" of H ₂ O) ml / sec |
|--------------------------|---|--|--|
| .070 / 1.778 | 24 / 610 / .87 | 17 / 432 / .61 | 1 |
| .100 / 2.540 | 24 / 610 / .87 | 16 / 406 / .56 | 3 |
| .145 / 3.683 | 24 / 610 / .87 | 15 / 381 / .54 | 8 |
| .187 / 4.750 | 26 / 660 / .94 | 14 / 356 / .50 | 13 |

UNCONTROLLED, SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

