

V34 *SureFlo*[®] Valve

Description:

Capable of dispensing liquids, gases or powders at controlled dosages, the SureFlo[®] elastomeric valve is ideally suited for applications that require effective drip-proof, bi-directional or one-way flow control with few components or moving parts. This valve replaces multi-component ball and spring or other complex check valves & flow control valves.

Valve Characteristics:

- **Outside Diameter:** .500" (12.7 mm)
- **Material:** Silicone
- **Valve type:** V style, rolling sleeve
- **Opening pressure:** High
(low = 1"-16" (0-.58 PSI), medium = 17"-26" (.6 - .94 PSI) and high = 27" + (1 + PSI)
- **Unique Properties:** Good cut-off for thick product.
- **Applications:** Thick products like honey, chocolate sauce and children's sippy cups.

Related Documents:

- **Engineering drawing:** ECA-3547 (+REV)
- **Customer drawing:** CBA-3547 (+REV)
- **LMS project number:** 01-012

Valve Performance by Slit Size

SLIT SIZE inches / mm	OPEN (H ₂ O Column Height) inches / mm / PSI	CLOSE (H ₂ O Column Height) Inches / mm / PSI	Constant Flow (@ 30" of H ₂ O) ml / sec
.070 / 1.778	38 / 965 / 1.37	25 / 635 / .90	1.1
.160 / 4.064	37 / 940 / 1.33	17 / 432 / .61	13.0
.220 / 5.588	37 / 940 / 1.33	10 / 254 / .36	22.4
.250 / 6.350	37 / 940 / 1.33	7 / 178 / .25	23.7

UNCONTROLLED, SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

