

V48 *SureFlo*[®] Valve

Description:

Capable of dispensing liquids, gases or powders at controlled dosages, the SureFlo[®] elastomeric valve is ideally suited for applications that require effective drip-proof, bi-directional or one-way flow control with few components or moving parts. This valve replaces multi-component ball and spring or other complex check valves & flow control valves.

Valve Characteristics:

- **Outside Diameter:** .500" (12.7 mm)
- **Material:** Silicone
- **Valve type:** V style, rolling sleeve
- **Opening pressure:** Medium
(low = 1"-16" (0-.58 PSI), medium = 17"-26" (.6 - .94 PSI) and high = 27" + (1 + PSI))
- **Unique Properties:** Foam Dispensing, Top Dispense Only, and Weak Containers.
- **Applications:** Body Wash, Motor Oil and other thin to medium viscosity products.

Related Documents:

- **Engineering drawing:** ECA-3953 (+REV)
- **Customer drawing:** CBA-3953 (+REV)
- **LMS project number:** 03-015

Valve Performance by Slit Size

SLIT SIZE inches / mm	OPEN (H ₂ O Column Height) inches / mm / PSI	CLOSE (H ₂ O Column Height) Inches / mm / PSI	Constant Flow (@ 30" of H ₂ O) ml / sec
.250-H / 6.350	19 / 483 / .69	9 / 229 / .32	11.8

UNCONTROLLED, SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

