

V58 *SureFlo*[®] Valve

Description:

Capable of dispensing liquids, gases or powders at controlled dosages, the SureFlo[®] elastomeric valve is ideally suited for applications that require effective drip-proof, bi-directional or one-way flow control with few components or moving parts. This valve replaces multi-component ball and spring or other complex check valves & flow control valves.

Valve Characteristics:

- **Outside Diameter:** .600" (15.24 mm)
- **Material:** Silicone
- **Valve type:** V style, rolling sleeve
- **Opening pressure:** High
(low = 1"-16" (0-.58 PSI), medium = 17"-26" (.6 - .94 PSI) and high = 27" + (1 + PSI))
- **Unique Properties:** High opening, Self-venting Flap
- **Applications:** Cleaning solutions and other applications requiring additional self-venting flap

Related Documents:

- **Engineering drawing:** ECA-4121 (+REV)
- **Customer drawing:** CBA-4121 (+REV)
- **LMS project number:** 03-111

Valve Performance by Slit Size

| SLIT SIZE inches / mm | OPEN (H ₂ O Column Height) inches / mm / PSI | CLOSE (H ₂ O Column Height) Inches / mm / PSI | Constant Flow (@ 40" of H ₂ O) ml / sec |
|--------------------------|---|--|--|
| .140 / 3.556 | 37 / 940 / 1.33 | 26 / 660 / .94 | 5.3 |

UNCONTROLLED, SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

