

# V6 *SureFlo*<sup>®</sup> Valve

## Description:

Capable of dispensing liquids, gases or powders at controlled dosages, the SureFlo<sup>®</sup> elastomeric valve is ideally suited for applications that require effective drip-proof, bi-directional or one-way flow control with few components or moving parts. This valve replaces multi-component ball and spring or other complex check valves & flow control valves.

## Valve Characteristics:

- **Outside Diameter:** .634" (16.1 mm)
- **Material:** Silicone
- **Valve type:** V style, rolling sleeve
- **Opening pressure:** Medium  
(low = 1"-16" (0-.58 PSI), medium = 17"-26" (.6 - .94 PSI) and high = 27" + (1 + PSI)
- **Unique Properties:** Easy feeling dispense with more control.
- **Applications:** This valve is best suited for Medium products like shampoo, body wash, lotion and sauces where more control is desired.

## Related Documents:

- **Engineering drawing:** ECA-3968 (+REV)
- **Customer drawing:** CBA-3968 (+REV)
- **LMS project number:** 01-110

## Valve Performance by Slit Size

SLIT SIZE inches / mm	OPEN (H <sub>2</sub> O Column Height) inches / mm / PSI	CLOSE (H <sub>2</sub> O Column Height) Inches / mm / PSI	Constant Flow (@ 30" of H <sub>2</sub> O) ml / sec
.130 / 3.302	17 / 432 / .61	12 / 305 / .43	8.3
.187 / 4.750	17 / 432 / .61	11 / 279 / .40	13.2
.220 / 5.588	17 / 432 / .61	11 / 279 / .40	16.5
.250 / 6.350	18 / 457 / .65	10 / 254 / .36	19.5
.280 / 7.112	17 / 432 / .61	10 / 254 / .36	21.7
.320 / 8.128	18 / 457 / .65	9 / 229 / .32	26.0

UNCONTROLLED, SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

