

V66 *SureFlo*® Valve

Description:

Capable of dispensing liquids, gases or powders at controlled dosages, the SureFlo® elastomeric valve is ideally suited for applications that require effective drip-proof, bi-directional or one-way flow control with few components or moving parts. This valve replaces multi-component ball and spring or other complex check valves & flow control valves.

Valve Characteristics:

- **Outside Diameter:** .290" (7.37 mm)
- **Material:** Silicone
- **Valve type:** V style, rolling sleeve
- **Opening pressure:** High
(low = 1"-16" (0-.58 PSI), medium = 17"-26" (.6 - .94 PSI) and high = 27" + (1 + PSI)
- **Unique Properties:** Small Doses.
- **Applications:** Soap dispensing and medium viscosity products such as shampoo, conditioner, and body wash.

Related Documents:

- **Engineering drawing:** ECA-4357 (+REV)
- **Customer drawing:** CBA-4357 (+REV)
- **LMS project number:** 02-137

Valve Performance by Slit Size

SLIT SIZE inches / mm	OPEN (H ₂ O Column Height) inches / mm / PSI	CLOSE (H ₂ O Column Height) Inches / mm / PSI	Constant Flow (@ 60" of H ₂ O) ml / sec
.120 / 3.048	46 / 1168 / 1.66	20 / 508 / .72	4.2

UNCONTROLLED, SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

